



PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau


INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04N 7/28	A2	(11) International Publication Number: WO 97/46020 (43) International Publication Date: 4 December 1997 (04.12.97)
<p>(21) International Application Number: PCT/IB97/00547</p> <p>(22) International Filing Date: 14 May 1997 (14.05.97)</p> <p>(30) Priority Data: 96201462.7 24 May 1996 (24.05.96) EP (34) Countries for which the regional or international application was filed: NL et al. PCT/IB96/01382 6 December 1996 (06.12.96) WO (34) Countries for which the regional or international application was filed: CH et al.</p> <p>(71) Applicant: PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).</p> <p>(71) Applicant (for SE only): PHILIPS NORDEN AB [SE/SE]; Kottbygatan 7, Kista, S-164 85 Stockholm (SE).</p> <p>(72) Inventors: DE HAAN, Gerard; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). LO MUZIO, Pierluigi; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). SCHUTTEN, Robbert, Jan; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).</p> <p>(74) Agent: STEENBEEK, Leonardus, J.; Internationaal Octrooibureau B.V., P.O. Box 220, NL-5600 AE Eindhoven (NL).</p>		<p>(81) Designated States: JP, KR, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).</p> <p>Published Without international search report and to be republished upon receipt of that report.</p>

(54) Title: MOTION VECTOR PROCESSING

(57) Abstract

In a method of furnishing output motion vectors (MV'), motion vectors (MV) are retrieved (DEC) from an encoded image signal (MPEG), and the retrieved motion vectors (MV) are post-processed to obtain the output motion vectors (MV'). The post-processing includes generating (CVG) candidate motion vectors, and selecting (CVS) the output motion vectors (MV') in dependence upon the candidate motion vectors and the retrieved motion vectors (MV).



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

Motion vector processing.

The invention relates to a method and device for furnishing motion vectors, and to an image signal processing apparatus and an image display apparatus incorporating such a motion vector processing device.

5

DE-A-195.10.389 discloses a method and a circuit arrangement for receiving coded video signals. The method concerns a video signal which contains a sequence of images with compressed redundancy, e.g. coded in accordance with the MPEG2-standard. The motion decoding is carried out first. The post-processing of the motion-decoded fields, which post-processing essentially contains interpolations, is carried out next together with the processing to remove flicker. Advantageously, the motion vectors retrieved at the motion decoding, are used also for the flicker removal.

Motion estimation can be seen as an optimization problem: a sometimes complex, but usually simple criterion function has to be minimized or maximized to find an output motion vector. There are brute force methods that simply try all possible vectors, in a predefined range, in order to be sure to obtain the global optimum of the criterion function. Also there are efficient approaches that test only the most likely motion vectors. This likelihood is usually determined by spatial or temporal proximity, and consequently temporal and spatial prediction vectors have been popular in the efficient motion estimation algorithms. Depending on the motion estimation algorithm used, the properties of the resulting motion vector fields are different, so that the application areas of the various motion estimation algorithms are different. Motion vectors can be used in high quality video signal processing, like motion compensated scan conversion, motion compensated noise reduction and image coding. The intended processing puts constraints on various quality aspects of the motion vectors. For example, high quality motion compensated scan conversion requires a motion vector field where the vectors represent the true motion vectors (i.e., true direction and speed) within the image sequence. For coding applications this is irrelevant, as the only quality criterion is a low average prediction error.

20
25

Brute force methods like full search block matching tend not to give true motion

vectors. Instead, full search block matching minimizes the error between blocks, so its vectors will connect two blocks that have a minimal error between these two blocks, which is suitable for minimizing the prediction error in coding applications. While these minimal errors work efficiently for compression algorithms like MPEG, the resulting vectors are unsuitable for use in high quality scan conversion. On the other hand, more efficient motion estimators like 3-D recursive block matching tend to give true motion vectors that can be used in high quality scan conversion but which may not be suitable for use in compression algorithms.

With the emergence of MPEG and other types of video compression it is possible to have input video material that already contains motion vectors, so at first sight it may seem that for this type of source material motion estimation at the receiver side is not necessary. However, it is not certain that these motion vectors can be directly used for e.g. scan rate conversion, because it is unknown whether the MPEG motion vectors represent true motion or not. At the decoder/receiver side it is unknown what type of motion estimation algorithm was used at the encoder/transmitter side, so one must assume, as a worst case situation, that the MPEG motion vectors are optimized for an efficient compression and that they do not represent true motion vectors. For example, a homogeneous background could produce strange and long inconsistent vectors when small changes of brilliance happen in a heterogeneous way. More specifically, periodical structures and noise in picture areas with little detail, may cause such inconsistent vectors. Another problem with motion vectors in MPEG data streams is that it is uncertain that all motion vectors are transmitted within the data stream. For these reasons, the technique proposed by DE-A-195.10.389 seems not to be suitable for high quality post-processing.

In an attempt to solve a similar problem, it has been proposed to smooth the vectors transmitted with a digitally encoded television signal before using these vectors for a field rate upconversion operation, see the M.S.E.E. graduation report "Bewegingsgecompenseerde interpolatie van digitale televisiebeelden", by L.J. Steenbeek, Delft University of Technology, December 1986, pp. 60-68.

30

It is, *inter alia*, an object of the invention to furnish motion vectors which are suitable for high quality post-processing. To this end, a first aspect of the invention provides a method as defined by claim 1. A second aspect of the invention provides a device as defined by claim 4. A third aspect of the invention provides an image signal processing

apparatus as defined by claim 5. A fourth aspect of the invention provides an image display apparatus as defined by claim 6. Advantageous embodiments are defined in the dependent claims.

In a method of furnishing output motion vectors in accordance with a primary aspect of the present invention, motion vectors are retrieved from an encoded image signal, and the retrieved motion vectors are post-processed to obtain the output motion vectors. The post-processing includes generating candidate motion vectors, and selecting the output motion vectors in dependence upon the candidate motion vectors and the retrieved motion vectors.

These and other aspects of the invention will be apparent from and elucidated with reference to the embodiments described hereinafter.

In the drawings:

Fig. 1 illustrates in a schematic form various embodiments of an image display apparatus having a motion vector furnishing device in accordance with the present invention; and

Fig. 2 discloses a H261/263 decoder with post-processing in accordance with the present invention.

20

The problems described in the above background part do not exclude the MPEG motion vectors entirely from use in high quality scan conversion. When an appropriate post-processing is applied, the MPEG motion vectors can be made useful. More specifically, when the receiver is able to determine the quality of the MPEG motion vectors, and when it is able to improve the quality of the MPEG motion vectors so that they meet certain criteria for the intended processing, the MPEG motion vectors can be used. Several possible post processing methods to extend the applicability of the MPEG motion vectors are considered:

1. Process the MPEG motion vectors with an operation like some sort of vector smoothing operation to increase the usability of the MPEG motion vectors.
2. Use the MPEG motion vectors as additional candidates along with spatial and/or temporal candidates in, for instance, a 3-D recursive block matching algorithm, similar to the use of an additional parametric vector candidate as disclosed in the non-published EP patent application no. 96201462.7 filed on 24.05.96 and in any corresponding patent applications, incorporated by reference herein (attorney's docket PHN 15,824). For a

description of an efficient recursive motion vector estimation algorithm which obtains motion vectors on the basis of several candidate vectors, reference is also made to the articles by Dr. G. de Haan et al. listed at the end of the description of the non-prepublished EP patent application no. 96201462.7.

- 5 3. The MPEG motion vectors can be used to calculate the parametric vector candidates described in the non-prepublished EP patent application no. 96201462.7.

For a schematic description of the various embodiments, reference is made to Fig. 1.

- 10 Fig. 1 shows a basic section B, and four sections E1 .. E4 showing four distinct ways to augment the basic section B to obtain four distinct embodiments B+E1, B+E2, B+E3, and B+E3+E4 of an image display apparatus.

- In the basic section B, an MPEG signal comprising a video signal V and motion vectors MV, is applied to a decoder DEC in order to retrieve the video signal V in
15 dependence upon the motion vectors MV from the MPEG input signal. The video signal V is applied to a video post-processor VPP to obtain an output video signal OVS having a doubled field frequency and/or line frequency or an improved motion portrayal with respect to the video signal V. Alternatively or in addition, the video post-processor VPP reduces noise and/or changes the number of pixels per line and/or lines per field of the video signal
20 V. The video post-processing carried out by the processor VPP is dependent on improved motion vectors MV'. The output video signal OVS is displayed on a display device D.

- In accordance with a first embodiment B+E1, the improved motion vectors MV' are obtained from the motion vectors MV contained in the MPEG signal by means of a post-processor PP. For example, a smoothing operation will reduce most of the artifacts
25 which would arise if the MPEG motion vectors MV were directly used for the video post-processing carried out by the processor VPP. A smoothing operation may include separate low-pass filtering operations on the horizontal and vertical components of the motion vectors. Alternatively, the horizontal and vertical components of the motion vectors can be applied to median filters to replace extreme motion vector component values by existing motion vector
30 component values of motion vectors of neighboring blocks of picture elements.

In accordance with a second embodiment B+E2 which is covered by the claims of the present patent application, the MPEG motion vectors MV are multiplexed by a multiplexer MUX with candidate vectors generated by a candidate vector generator CVG, optionally after a (e.g. smoothing) post-processing operation carried out by the post-

processor PP. The multiplexed vectors are applied to a candidate vector selector CVS to obtain improved motion vectors MV' which are expected to show the smallest errors.

In a third embodiment B+E3 which is covered by a copending patent application, a parameter extractor PE extracts motion parameters $p_1 \dots p_n$ from the MPEG
5 motion vectors MV. The motion parameters $p_1 \dots p_n$ are applied to a vector field calculator VFC to obtain the improved motion vectors MV'. Reference is again made to the non-prepublished EP patent application no. 96201462.7 and its corresponding applications for further details.

In a fourth embodiment B+E3+E4 which is covered by the claims of the
10 present patent application, the motion vectors calculated by the vector field calculator in section E3 are multiplexed with candidate motion vectors from the candidate vector generator CVG, and applied to the candidate vector selector CVS to obtain the improved motion vectors MV'. This fourth embodiment combines the features of the second and third
embodiments.

15

Obviously, the present invention is not limited to MPEG signals; other signals like H261 or H263 signals can be treated in the same manner. Fig. 2 discloses a H261/263 decoder with post-processing in accordance with the present invention. A H261 or H263 input signal is applied to a demultiplexer DEMUX to obtain a digital video signal DV and
20 motion vectors MVE. The motion vectors MVE are applied to a variable length decoder VLC^{-1} to obtain decoded motion vectors MV. The digital video signal DV is applied to a cascade connection of a variable length decoder VLC^{-1} , an inverse quantizer Q^{-1} , and a discrete cosine transform (DCT) decoder DCT^{-1} , to obtain a video difference signal VDS. The video difference signal VDS and the motion vectors MV are applied to a prediction
25 block PR, whose output is added to the video difference signal VDS to obtain the decoded video signal V. The decoded video signal V and the motion vectors MV are applied to a recursive motion estimator RME to obtain improved motion vectors MV' in dependence on which the decoded video signal V is processed by a motion-compensated interpolator MCI to obtain an output video signal OVS. In a sequence of coded images comprising intra-frame
30 coded images (which stand alone), predictively coded images (which can be decoded by means of a preceding intra-frame decoded image or a preceding decoded predictively coded image, and the motion vectors MV), and bi-directionally coded images between an intra-frame coded image and a predictively coded image or between two predictively coded images, the improved motion vectors MV' are preferably used to decode (i.e. interpolate) the

bi-directionally coded images.

The embodiment of Fig. 2 can be implemented on a PC add-on card in a multi-media PC.

5 The basic considerations underlying a primary aspect of the present invention can be summarized as follows. Different motion estimation algorithms will have different applications based on the properties of their resulting vector fields. MPEG video data streams contain motion vectors, which can possibly be used in high quality video processing. However, it is likely that these MPEG motion vectors are optimized to achieve an efficient
10 compression, so that these vectors cannot be expected to represent the true motion. This means that additional processing is needed to improve their quality and usability for a high quality post-processing. It is proposed to process the MPEG motion vectors at the receiver side. For instance, they can be used as additional candidate vectors in an efficient motion estimator. In this manner, the applicability of MPEG motion vectors is extended.

15 The following salient features of preferred embodiments of the present invention can be mentioned. A post-operation on motion vectors, that are received along with a video signal, intended to further increase a quality aspect of said vectors like e.g. their spatial and/or temporal smoothness, so that they can be used for high quality video signal processing. A post operation on motion vectors, that are received along with a video signal,
20 where the motion vectors are used, possibly after a post processing, as additional candidates for some, or all, of the blocks in an efficient motion estimator that uses a limited set of possible vector candidates. An operation where the motion vectors are used to generate the parameters of a parametric model that describes the global motion within the video sequence. An operation where these extracted parameters are used to generate additional candidates for
25 some, or all, of the blocks in an efficient motion estimator that uses a limited set of possible vector candidates.

 It should be noted that the above-mentioned embodiments illustrate rather than limit the invention, and that those skilled in the art will be able to design many alternative embodiments without departing from the scope of the appended claims. In the claims, any
30 reference signs placed between parentheses shall not be construed as limiting the claim. The invention can be implemented by means of hardware comprising several distinct elements, and by means of a suitably programmed computer. Reference is made to copending patent applications for features disclosed but not claimed in this application.

Claims:

1. A method of furnishing output motion vectors (MV'), the method comprising the steps of:
 - retrieving (DEC; DEMUX, VLC⁻¹) motion vectors (MV) from an encoded image signal (MPEG; H261, H263); and
 - 5 post-processing (RME) the retrieved motion vectors (MV) to obtain the output motion vectors (MV'), wherein the post-processing step (RME) includes the steps of:
 - generating (CVG) candidate motion vectors; and
 - selecting (CVS) said output motion vectors (MV') in dependence upon said candidate motion vectors and said retrieved motion vectors (MV).
- 10 2. A method as claimed in claim 1, wherein the post-processing step (RME) includes the step of subjecting said retrieved motion vectors (MV) to a smoothing operation (PP) to obtain smoothed vectors, and where in said selecting step (CVS), said output motion vectors (MV') are selected from said candidate motion vectors and said smoothed vectors.
- 15 3. A method as claimed in claim 1, wherein the post-processing step (RME) includes the steps of:
 - extracting (PE) motion parameters (p1 .. pn) from said retrieved motion vectors (MV);
 - 20 calculating parametric motion vectors in dependence upon said motion parameters (p1 .. pn); and
 - where in said selecting step (CVS), said output motion vectors (MV') are selected from said candidate motion vectors and said parametric motion vectors.

4. A device for furnishing output motion vectors (MV'), the device comprising:
 means for retrieving (DEC; DEMUX, VLC⁻¹) motion vectors (MV) from an
 encoded image signal (MPEG; H261, H263); and
 means for post-processing (RME) the retrieved motion vectors (MV) to obtain
5 the output motion vectors (MV'), wherein the post-processing means (RME) include:
 means for generating (CVG) candidate motion vectors; and
 means for selecting (CVS) said output motion vectors (MV') in dependence
 upon said candidate motion vectors and said retrieved motion vectors (MV).
- 10 5. An image signal processing apparatus, comprising:
 an output motion vector furnishing device (DEC, PP; DEMUX, VLC⁻¹, RME)
 as claimed in claim 4;
 means (DEC; VLC⁻¹, Q⁻¹, DCT⁻¹, PR) for providing a decoded image signal (V)
 in response to said encoded image signal (MPEG; H261, H263); and
15 means for post-processing (VPP; MCI) said decoded image signal (V) in
 dependence upon said output motion vectors (MV'), to obtain a post-processed image signal
 (OVS).
- 20 6. An image display apparatus, comprising:
 an image signal processing apparatus as claimed in claim 5; and
 means (D) for displaying said post-processed image signal (OVS).




FIG. 1




FIG. 2




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : H04N 7/36, 7/28	A3	(11) International Publication Number: WO 97/46020 (43) International Publication Date: 4 December 1997 (04.12.97)
(21) International Application Number: PCT/IB97/00547 (22) International Filing Date: 14 May 1997 (14.05.97) (30) Priority Data: 96201462.7 24 May 1996 (24.05.96) EP (34) Countries for which the regional or international application was filed: NL et al. PCT/IB96/01382 6 December 1996 (06.12.96) WO (34) Countries for which the regional or international application was filed: CH et al. (71) Applicant: PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL). (71) Applicant (for SE only): PHILIPS NORDEN AB [SE/SE]; Kottbygatan 7, Kista, S-164 85 Stockholm (SE). (72) Inventors: DE HAAN, Gerard; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). LO MUZIO, Pierluigi; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). SCHUTTEN, Robbert, Jan; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). (74) Agent: STEENBEEK, Leonardus, J.; Internationaal Octrooibureau B.V., P.O. Box 220, NL-5600 AE Eindhoven (NL).		(81) Designated States: JP, KR, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i> (88) Date of publication of the international search report: 22 January 1998 (22.01.98)

(54) Title: MOTION VECTOR PROCESSING**(57) Abstract**

In a method of furnishing output motion vectors (MV'), motion vectors (MV) are retrieved (DEC) from an encoded image signal (MPEG), and the retrieved motion vectors (MV) are post-processed to obtain the output motion vectors (MV'). The post-processing includes generating (CVG) candidate motion vectors, and selecting (CVS) the output motion vectors (MV') in dependence upon the candidate motion vectors and the retrieved motion vectors (MV).



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

INTERNATIONAL SEARCH REPORT

International application No.

PCT/IB 97/00547

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: H04N 7/36, H04N 7/28

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: H04N

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 0615386 A2 (THOMSON CONSUMER ELECTRONICS, INC.), 14 Sept 1994 (14.09.94), column 5, line 1 - line 48, figure 1 --	1,4,5
A	US 5515114 A (E. MURATA), 7 May 1996 (07.05.96), abstract --	1,4,5
A	EP 0578290 A1 (PHILIPS ELECTRONICS N.V.), 12 January 1994 (12.01.94), abstract --	1,4
P,A	DE 19510389 A1 (SIEMENS AG), 2 October 1996 (02.10.96), the whole document -- -----	1-6

☐ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"B" earlier document but published on or after the international filing date

"I" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

21 November 1997

Date of mailing of the international search report

25 -11- 1997

Name and mailing address of the ISA/

Swedish Patent Office

Box 5055, S-102 42 STOCKHOLM

Facsimile No. +46 8 666 02 86

Authorized officer

Christian Rasch

Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT
Information on patent family members

01/10/97

International application No.
PCT/IB 97/00547

Patent document cited in search report			Publication date	Patent family member(s)		Publication date
EP	0615386	A2	14/09/94	CA	2114401 A	13/09/94
				CN	1095878 A	30/11/94
				JP	7050842 A	21/02/95
				US	5508744 A	16/04/96
US	5515114	A	07/05/96	JP	2591441 B	19/03/97
				JP	7099657 A	11/04/95
EP	0578290	A1	12/01/94	JP	7282267 A	27/10/95
DE	19510389	A1	02/10/96	NONE		

BEST AVAILABLE COPY